(11) Publication number: 04036394 A

(43) Date of publication of application: 06.02.92

(51) Int. CI

C11D 1/94

A61K 7/075 C11D 3/37

//(C11D 1/94 , C11D 1:28 , C11D 1:88 )

(21) Application number: 02143643

(71) Applicant:

KAO CORP

(22) Date of filing: 01.06.90

(72) Inventor:

IMAMURA TAKASHI YAMASHINA SAHOKO KUMAGAI SEIICHI

YAHAGI KAZUYUKI

### (54) DETERGENT COMPOSITION

### (57) Abstract:

PURPOSE: To provide a detergent excellent in detergency and various conditioning effects by combining an amido-amine amphoteric surfactant, sulfosuccinate anionic surfactant and two kinds of specific high-molecular silicones.

CONSTITUTION: A detergent composition is prepared by mixing an amido-amine amphoteric surfactant (A) [e.g.

N-lauroyl-N'-carboxylmethyl-N'-(2-hydroxyethyl) ethylenediamine], a sulfosuccinate anionic surfactant (B) (e.g. sulfosuccinate of lauryl alcohol), polyoxyalkylene-modified organopolysiloxane (C) containing 3-30wt.% polyoxyalkylene groups in the molecule and capable of dispersing in water, and a

containing 3-30wt.% polyoxyalkylene groups in the molecule and capable of dispersing in water, and a nonvolatile polysiloxane (D) having a viscosity of 5,000cSt or more at 25°C except the component C. The detergent composition is preferably used in shampoo, etc.

COPYRIGHT: (C)1992,JPO&Japio

(11) Publication number: 04144592 A

(43) Date of publication of application: 19.05.92

(21) Application number: 02266932

(22) Date of filing: 03.10.90

(71) Applicant: MATSUSHITA ELECTRIC IND COLTD

(72) Inventor: KUMAGAI SHINICHI OKANISHI SATORU AWAZU MITSUAKI

### (54) LAUNDRY NET


# (57) Abstract:

PURPOSE: To prevent adhesion of powder detergent particles to the surface of a quilt or a blanket put in a laundry net by making the upper part of the laundry net with water permeable cloth which does not let powder detergent particles pass through.

CONSTITUTION: An upper part cloth 10 of a laundry net 11, made of net cloth, in which a quilt, a blanket, or other large clothing is put is made of water permeable cloth which rejects the passage of powder detergent particles. A quilt or a blanket is put in the laundry net 11, and a fastener 14 is closed. Then, the laundry net 11 is put in a washing cylinder in which detergent is put in in advance in a manner that the fastener 14 faces upward. When the upper part of the laundry net 11 is sufficiently sprayed with a water-detergent mixture, the upper part cloth 10, which is made of water permeable cloth which rejects powder detergent particles. Powder detergent particles that have not dissolved completely do not adhere to the quilt or the blanket in the laundry net 11. Since a small air vent hole 15 is provided, the laundry net 11 does not float even if air comes out of clothing containing air inside

due to rotation during washing.

COPYRIGHT: (C)1992, JPO& Japio



(11) Publication number: 05239493 A

(43) Date of publication of application: 17.09.93

(51) Int. CI

C11D 1/86 //(C11D 1/86 , C11D 1:68 , C11D 1:62 , C11D 3:37 , C11D 1:22 , C11D 1:29 )

(21) Application number: 04043368

(71) Applicant:

**KAO CORP** 

(22) Date of filing: 28.02.92

(72) Inventor:

**TAGATA HIDEJI** 

IWAMOTO YOSHIHIRO ISHIKURA AKIKO

**SAI FUMIO** 

(54) LIQUID DETERGENT COMPOSITION FOR **CLOTHES** 

COPYRIGHT: (C)1993, JPO& Japio

(57) Abstract:

PURPOSE: To prepare the subject composition improved in detergency by mixing a specified alkyl glycoside, cationic surfactant, aminated silicone (derivative) and anionic surfactant.

CONSTITUTION: 5-70wt.% alkyl glycoside of formula I

[wherein R<sub>1</sub> is linear or branched 8-18C alkyl (phenyl) or alkenyl; R2 is 2-4C alkylene; G is a residue of a 5-6C reducing sugar; (x) is 0 to 5 on average; and (y) is 1 to 10 on average] is mixed with 0.5-10wt.% cationic surfactant of formula II [wherein at least one of  $R_3$  to R<sub>6</sub> is 14-20C alkyl, and the rest are each 1-5C (hydroxy) alkyl or (CH2CH2O)m-H; (m) is such a number that the average number of ethylene oxide molecules added is 2 to 30 in the molecule; and x is halogen, CH<sub>3</sub>SO<sub>4</sub> or CH<sub>3</sub>CH<sub>2</sub>SO<sub>4</sub>], 0.05-5wt.% aminated silicon

(derivative) having a molecular weight of 2,000 to 15,000 and 0.5-10wt.% of at least one anionic surfactant

selected from alkylbenzene sulfates, etc.

 $R_1 (0R_2)_T G_V$ 

X-П

(11) Publication number: 06065803 A

(43) Date of publication of application: 08.03.94

(51) Int. CI

A41D 31/00

D06M 13/11

D06W 15/423

D06M 15/643

(21) Application number: 03039384

(71) Applicant:

KANEBO LTD

(22) Date of filing: 07.02.91

(72) Inventor:

**TORIYAMA SHIGESATO** 

**IWATA YOSHIKO** 


# (54) WASHING-RESISTANT SILK CLOTHES

### (57) Abstract:

PURPOSE: To provide the subject clothes developing no wrinkle or no shortened yarn abnormality on its face fabric even if washed.

CONSTITUTION: The objective clothes can be obtained by using a special washable silk fabric as the face fabric treated with (A) an epoxy compound, (B) a silicone resin, and (C) an aminoplast resin and/or glyoxal resin and having  $\le 3\%$  of washing shrinkage rate in the warp direction and  $\leq$ -3% of that in the weft direction and by jointing core fabrics of -2.5 to -0.1% washing shrinkage rate in the weft direction to specified sites.

COPYRIGHT: (C)1994,JPO&Japio



**Business** Information Services

ITC Library

L68 ANSWER 69 OF 119 WPIDS COPYRIGHT 1999 DERWENT INFORMATION LTD

FAMILY 35

ACCESSION NUMBER:

95-190972 [25] WPIDS

DOC. NO. NON-CPI:

N95-149840

DOC. NO. CPI:

C95-088667

TITLE:

Efficient cleaning of clothes for laundry - using

liq. detergent contg oxyethylene-oxypropylene copolymer added type silicone oil(s) and liq

cleaning auxiliaries.

DERWENT CLASS:

A26 A97 D25 X27

PATENT ASSIGNEE(S):

(LIOY) LION CORP

COUNTRY COUNT:

1

PATENT NO KIND DATE WEEK LA PG MAIN IPC

PATENT INFORMATION:

JP 07109486 A 950425 (9525)\* 5 C11D001-82

<--

APPLICATION DETAILS:

PATENT NO KIND

APPLICATION

DATE

JP 07109486 A

JP 93-258132 931015

PRIORITY APPLN. INFO: JP 93-258132 931015

INT. PATENT CLASSIF.:

MAIN:

C11D001-82

SECONDARY:

D06F039-02

AN

95-190972 [25] WPIDS JP07109486 A UPAB: 950630

Cleaning clothes uses a continuous vertical inner-body-rotating washing machine having at least two separate washing vessels and operating by washing clothes in the first vessel, discharging the cleaning soln. in the vessel, transferring clothes to the next vessel to washing again and so on. It is characterised by addn. of (A) a liq. detergent contg. an oxyethylene-propylene copolymer added type silicone oil(s) and a surfactant(s) and (B) a liq. cleaning auxiliary(ies) based on a chelating and/or an alkali agent(s) to the vessels.

USE/ADVANTAGE - The method is useful for cleaning laundry. The method achieves high cleaning performance and efficiency.

In an example, the silicone oil of (A) is usually prepd. by adding an oxyethylene-oxypropylene copolymer to dimethyl siloxane. The blend ratio of the oil is usually 0.01-10 wt.%, pref. 0.1-5 wt.%. Available surfactants for (A) include nonionic, anionic and amphoteric. The blend ratio of surfactants is usually 3-50 wt.%, pref. 5-30 wt.%. Typical chelating agents include the phosphate, aluminosilicate, polycarboxylic and amino polycarboxylic types. Dwg.0/0

This Page Blank (uspto)